











User Management in APP

Device Sharing

Opening Record

Remotely Open

DoorBell Call Notice

The device is an Access Controller with WiFi-enabled Intercom. People can install the APP for intercom with their smart phone. It's integrated with Tuya which supports 500 mobile users and 1000 local users.

## Features:

- > Metal case, anti-vandal
- > Waterproof, conforms to IP65
- > Video calling based on WiFi
- > Full duplex voice intercom
- > One relay, 1,000 users (990 common + 10 visitor)
- > Pulse mode, Toggle mode

- > PIN length: 4~6 digits
- > Card type:125KHz EM Card
- > Can be used as Wiegand reader with buzzer output
- > Card block enrollment
- > Tri-color LED status display

## **Specification:**

User Capacity Common User	<b>1000</b> 900 (Fingerpint version support 100 fingerprints)
Visitor User	10
Operating Voltage	12~18V DC
Working Current Idle Current	≤150mA ≤60mA
Proximity Card Reader Radio Technology Read Range	EM 125KHz 2~6 cm
PIN Length	4~6 digits (Keypad version only)
Wiring Connections	Relay Output, Exit Button, Wiegand Input, Wiegand Output
Relay	One (NO, NC, Common)
Adjustable Relay Output	0~99 Seconds (5 seconds default)
Time Lock Output Load	2 Amp Maximum
Wiegand Interface	Wiegand 26~44 bits input & output (Factory Default: Wiegand 26bits)
PIN Output (Keypad version only)	4 bits, 8 bits(ASCII), 10 digits Virtual Number (Factory Default: 4 bits)
Environment	Meets IP65
Operating Temperature	-40°C~60°C(-40°F~140°F)
	-30°C~60°C(-22°F~140°F) Fingerprint only
Operating Humidity	0%RH~92%RH
Physical	Zinc-Alloy
Colour	Silver & Black
Dimensions	142 x 48 x 22mm
Unit Weight	315g
Shipping Weight	410g

