

R-VWC0109-R EVO

Erbu HDMI Video Wall Controller



Technical Specification

Items	Description	
Video Signal	HDMI Input	1x HDMI
	HDMI Output	9x HDMI
	Compatibility	HDMI 2.0 HDCP 1.4 / HDCP 2.2
	Resolutions	Input: 4096x2160@24/25/30/50/60Hz, 3840x2160@24/25/30/50/60Hz, 3440x1440@60Hz, 2560x1600@60Hz, 2560x1440@60Hz, 2560x1080@60Hz, 2048x1536@60Hz, 1920x1200@60Hz, Output: When the mode is 0000/0001/0010, the maximum output is 1080P@30Hz; other modes have a maximum output of 1080P@60Hz. Input: 1080P@24/25/30/50/60Hz Output: 1080P@30/60Hz
Video Signal	3,5 mm Output	PCM
	S/PDIF Output	PCM
	HDMI Output	PCM
Splice Settings	Mode	1x2 / 1x3 / 1x4 / 2x2 / 2x3 / 3x2 / 2x4 / 4x2 / 3x3
	DIP Switch	
Power	Power Supply	DC12V / 2A
	Power Consumption	<18W
Operating Environment	Working temperature	-20°C~60°C
	Storage temperature	-30°C~70°C
	Humidity	0~90%RH (No condensation)
Physical Properties	Housing	Iron
	Weight	775g
Physical Properties	Color	Black
	Dimensions	265(L)*105(W)*25(H)mm
Protection	ESD protection	1a Contact discharge level 2 (±4KV) 1b Air discharge level 3 (±8KV) Implementation of the standard: IEC61000-4-2
	Lightning protection, Surge protection	