

DESCRIPTION

The DA-250F is a 4-Channel Digital Power Amplifier featuring lightweight, compact, high power output, and high efficiency. It delivers 250 W × 4 channels (4 Ω output) using a switching power supply. Each channel is equipped with an independent power section. It can be mounted in an EIA Standard equipment rack (1 unit size).

SPECIFICATIONS

*0 dB = 0.775 V

Power Source	220 – 240 V AC, 50/60 Hz
Amplification System	Digital Class D
Power Consumption	200 W (based on EN standards) 1200 W (rated output 4 Ω × 4) 800 W (rated output 8 Ω × 4)
Input	4 circuits, +4 dB* (1.23 V) (input level control in maximum position), 10 kΩ, electronically-balanced, removable terminal block (3 pins) CH 1 mode ON/OFF switch (ON: CH 1 to All ch, OFF: Each ch)
Rated Output	4 channels: 250 W × 4 (4 Ω), 170 W × 4 (8 Ω) 2 channels (BRIDGE): 500 W × 2 (8 Ω) M4 screw terminal, distance between barriers: 8.8 mm
Frequency Response	20 – 20,000 Hz (±1 dB)
Total Harmonic Distortion	0.1% (1 kHz) 0.3% (20 – 20,000 Hz)
Protection Circuit	Protection against excessive current flow due to overload, short circuit, unusual DC voltage output, and heat sink temperature rise (over 110°C)
S/N Ratio	100 dB (A-weighted)
Crosstalk	70 dB (A-weighted)
LED Indicator	Power (blue) × 1, Input (green) × 4, Output (yellow) × 4, Peak (red) × 4, Protect (red) × 4
Cooling	Forced air cooling
Operating Temperature	-10°C to +40°C
Operating Humidity	Under 90% RH (no condensation)
Finish	Panel: Aluminum, black, alumite Case: Plated steel sheet
Dimensions	482 (W) × 44 (H) × 401.8 (D) mm
Weight	6.8 kg
Accessory	Power cord (2 m) ...1, Removable terminal plug (3 pins) ...4, Tamper-proof cap ...4, Rack mounting screw (with plain washer) ...4

APPEARANCE

